



RECOMMENDED P. C. B LAYOUT(PCB THICKNESS: 1.6mm)
COMPONENT SIDE VIEW(TOLERANCE: ±0.05)

NOTES:

1. MATERIAL:
 - 1.1 HOUSING: LCP, UL94V-0, COLOR: BLACK
 - 1.2 CONTACT: BRASS, SQ. 1.05mm.
2. FINISH:
 - 2.1 CONTACT: (120u" MIN) BRIGHT TIN PLATED OVER Ni(50u" MIN.) UNDERPLATED OVERALL.
3. SPECIFICATION:
 - 3.1 CURRENT RATING: 9AMPS.
 - 3.2 VOLTAGE RATING: 250VAC.
 - 3.3 CONTACT RESISTANCE: 20mΩ MAX.
 - 3.4 INSULATION RESISTANCE: 1000MΩ MIN.
 - 3.5 TEMPERATURE RANGE: -25°C TO +85°C.
4. RESISTANCE TO SOLDERING HEAT: 265°C FOR 5 SECONDS.

PART NO:

63 1 - A 08 - 3 19 - L
 63 : ATX PITCH 4.20mm
 1 : FOR 90° DIP

 A : FOR BLACK
 08 : FOR 8 PIN

 3 : MIDDLE
 19 : SERIES NO.

 L : FOR LEAD FREE

廷奕科技股份有限公司
 VITETECH CO., LTD

REV.	ECN. NO.	APP.	DATE
		OW	MAY/25/11
REVISION	DESCRIPTION	APPROVE	DATE
A		JACK	
DRAW	CHK'D	APPROVE	DATE
OW	JACK	ALAN	MAY/25/11

RoHS COMPLIANT			
DIMENSION CLASSIFICATION			
◎:CRITICAL ⊕:MAJOR ():REFERENCE			
REVISION	DESCRIPTION	APPROVE	DATE
A		JACK	
DRAW	CHK'D	APPROVE	DATE
OW	JACK	ALAN	MAY/25/11

SCALE	1:1	SHEET	
GENERAL TOLERANCE			
X	±0.50	.X	±0.40
.XX	±0.35		
.XXX	±0.05		
X.		.X	
UNIT:MM			

PART NO:	631-A08-319-L
DWG NAME:	ATX POWER 2*4P R/A DIP 反向