



NOTES:

1. MATERIAL:

- 1.1 Housing: PBT UL 94V-0, Color: BLACK.
- 1.2 Cover: PBT UL 94V-0, Color: BLACK.
- 1.3 Contact: Brass(T=0.30mm)
- 1.4 Shell: Spcc(T=0.40mm)
- 1.5 Ring: Brass(T=0.40mm)

2. Finish:

- 2.1 Contact: Ag(80u") Plated
Ni(40u" min.) Underplated Overall.
- 2.2 Shell: Sn(80u" min.) Plated
CuSn(30u" min.) Underplated Overall.
- 2.3 Ring: CuSn(30u" min.) Plated

3. Characteristics:

- 3.1 Rating Voltage: 500V AC.
- 3.2 Rating Current: 20V DC AT 7.5A MAX.
- 3.3 Contact Resistance: 30 mΩMAX.
- 3.4 Insulation Resistance: 100 MΩMIN.
- 3.5 Withstanding Voltage: AC 500V.

PART NO:

- 71 1 - 4 C 5 - A 37 - H
- 71 : MID
- 1 : FOR SINGLE
- 4 : FOR 4 PIN
- C : FOR STEEL ALLOY
- 5 : FOR BLACK

- A : FOR Ag
- 37 : SERIES NO.

L : FOR LEAD FREE

廷奕科技股份有限公司
VITETECH CO., LTD

REV.	ECN. NO.	APP.	DATE
A	Official Publish	OW	MAY/25/11

RoHS COMPLIANT			
DIMENSION CLASSIFICATION			
Ⓞ : CRITICAL		Ⓜ : MAJOR () : REFERENCE	
REVISED	A		
DRAW	CHK' D	APPROVE	DATE
OW	JACK	ALAN	MAY/25/11

PRODUCT CUSTOMER COPY	
SCALE 1:1	SHEET
GENERAL TOLERANCE	
X. ±0.50	.X ±0.40
.XX ±0.35	
.XXX ±0.05	
X.'	.X'

PART NO: 711-4C5-A37-H
DWG NAME: DIN JACK 4P